

Code	Size	Brightness	Resolution	Inputs	Input Voltage	Remarks (IP Rating)
CDS-0009	12.1"	1000	1024x768	VGAX1, DVIx1, Compositex3, RS232x1, USBx1	DC input 9~36V	IP65 waterproof (facial) with console mounted
CDS-0010	15"	1000	1024x768	Audio phone jack (line-in, line-out, MIC-in), RJ45x2, USBx4, COMx2 (RS232x1, RS232/422/485x1) x1, DVI-Ix1, VGA-outx1, KB/MS PS2x1, power AC-inx3	AC Input 100~240V; DC input (optional)	IP65 waterproof (facial) with console mounted
CDS-0011	17"	1000	1280x1024	VGAX2, DVIx2, Compositex3, RS232x1, USBx1	DC input 9~36V	IP65 waterproof (facial) with console mounted
CDS-0012	19"	1000	1280x1024	Audio phone jack (line-in, line-out, MIC-in) x1, RJ45x2, USBx4, COMx2 (RS232x1, RS232/422/485x1), DVI-Ix1, VGA-outx1, KB/MS PS2x1, power AC-inx3	AC input: AC 100~240V; DC input (optional)	AC input: AC 100~240V; DC input (optional)
CDS-0013	21.5"	1000	1920x1080	VGAX2, DVIx2, Compositex3, RS232x1	DC input 9~36V	Fascial waterproof to IP65 standards when console mounted.
CDS-0014	24"	1000	1920x1080	VGAX2, DVIx2, Compositex3, RS232x1	DC input 9~36V	Fascial waterproof to IP65 standards when console mounted.